

### /// 3 AXLE 38,000L SINGLE-COMPT SEMI-TRAILER



<b>Technical Specifications</b>	HS33801OA0RE		
<b>Model &amp; Regulations</b>	NON-Code / TC406 HM Mixed Service, CMVSS 121 (Brake), CMVSS 108 (Electrical); ONT 413/O5 SPIF & CF149	<b>Lift Axles</b>	<i>Optional</i> Hendrickson UBL Lift axle with Wabco Control & Dual stage leveling valve
<b>Capacity &amp; Compt</b>	38,000L; 1 Compartment Insulated Trailer, Flanged and dished Bulkheads, 2 Baffles per Design	<b>Brakes</b>	Drum with 16.5" x 7" H23 Extended Svc lining, Duralite steel Hubs w/ Outboard (Centrifuse) Brake Drums
<b>Tank Outer Shell</b>	5454 H32 Alloy MILL Finish	<b>Wheels &amp; Tires</b>	8.25 x 22.5 Std Aluminum Wheels
<b>Tank Framing</b>	Alum Crossmembers		Michelin XTE 11R 22.5 14(G)
<b>Ring Stiffeners</b>	Aluminum extrusions, continuous weld	<b>ABS Brake System To CMVSS 121</b>	Wabco 4S/2M anti lock brake system (ABS)
<b>Insulation</b>	Fiberglass: around tank shell, Thickness: 150 mm (6"), when compressed 100 mm (4")	<b>Air Tanks &amp; Wiring</b>	All Aluminum Air Tanks per Design Colour-Coded Air Lines per SAE Std
<b>Manholes</b>	Betts PPVL720BXV 20" Manhole with 10" fill cover	<b>KP Plate</b>	Heavy Duty 3/8" Steel Construction w/ 2" King Pin & 3" Adjustable Bolt Holes
<b>Discharge System</b>	Betts, P/N 46924ALTS-051, 6" X 4" pneumatic EV Outlet at the rear of the trailer terminating with a 4" gate valve & aluminum camlock adapter/cap Dixon VR6035SQ Pneumatic Vapor Vent installed in a 6" Riser & relocated Betts 6496AL PPV Vent	<b>Landing Gear</b>	Holland Mark V 200,000 LBS Two Speed w/ Non-Removeable Handle
<b>Pump off line</b>	<i>Optional</i> - 4" aluminum piping plumbed from rear sump to the C/S front fender location. Terminating with a Betts EV46920ALTS030, gate valve & camlock adapter	<b>Paint</b>	Steel & Frame Components Powder Coated Black. L/G & Axles OEM Armor Guard Finish
<b>Thermometer</b>	One (1) 50°F to 500°F (- 10°C to 260°C) Range Installed on rear head at in an immersion well	<b>Electrical &amp; Lighting Systems CMVSS 108</b>	Truck-Lite LED Lighting System with Fit n' Forget Harness system
<b>Heating Coil</b>	<i>Optional</i> 2" aluminum pipes, single run in/out full length Maximum operation pressure: 100 PSI	<b>Aluminum Cabinet</b>	42" Curbside Storage & Operation Cabinet
<b>Suspension Frame</b>	Heavy Duty T100 & HLSA Steel Suspension Frame w/ Brackets for Huck Bolt-On Hanger Installation	<b>Other Accessories</b>	Aluminum Fenders; Aluminum Ladder, Aluminum Hose Tube & More
<b>Suspension Tridem Axle</b>	HENDRICKSON INTRAXX AAT25K 14" RH, HXL-3 Wheel end system, 25,000 LBS Capacity, Bolt-	<b>Documents</b>	All Test & Certifications Documents Completed & Provide to the Customer