

/// 4 AXLE 34,000L MULTI-COMPT TC 406 QUAD PUP TRAILER



Specification Sheet	AQFFT 340		
Model & Regulations	TC 406; ASME; CSA B620; CMVSS 121 (Brakes) CMVSS 108 (Electrical)	Brakes	Drum with 16.5" x 7" H23 Extended Svc lining, Duralite steel Hubs w/ Outboard (Centrifuse) Brake Drums
Capacity & Compt	34,000L; 2,3 & 4 Compartment B-Train Double Bulkheads w/ Baffles per Design	Wheels & Tires	8.25 x 22.5 Std Aluminum Wheels Michelin XTE 11R 22.5 14(G)
Tank Outer Shell Tank Framing	5454 H32 Alloy BTS Finish Alum Crossmembers & Outriggers per design	Wabco Brake System To CMVSS 121	ABS Wabco 2S/2M for the Lead & 2S/1M for the Pup
SUPER TANKER PKG Extended Warranty	SUPERTANKER 5 YEAR Limited Warranty on Dixon, Betts & Flotech Components	Air Tanks & Wiring	All Aluminum Air Tanks per Design Colour-Coded Air Lines per SAE Std
Manholes & Vents	Betts 20" 406-98 PAF Relief Manholes, Betts AVT 3.5" ALTS Sequential Air Vapour Vents	KP Plates	Heavy Duty 3/8" Steel Construction w/ 2" King Pin & 3" Adjustable Bolt Holes
Overfill Protection	FloTech Optic Overfill Sensors per Compartment, Includes provisions for future retain sensors & monit	Lift Axles & Tire Inflation	Provisions included for future installation of UBL lift axle w/ Wabco control system & Tiremax
Emergency Valves & Discharge System	Betts 4" Air Internal Valves w/ Tef-Sil Seals Dixon 4" API Adaptors w/ Baylast Seals	Landing Gear	N/A
Vapour Recovery System	Provision only. Outlet at the rear of the C/S overturn rail on the lead and pup	Paint	Steel & Frame Components Powder Coated Black. L/G & Axles OEM Armor Guard Finish
Piping System	4 1/2" Seamless Alum Sch 10 High Flow Piping Formed & Bent with Minimum Welding	Electrical & Lighting Systems CMVSS 108	Truck-Lite LED Lighting System with Fit n' Forget Harness system
Suspension Frame	Heavy Duty T100 & HLSA Steel Suspension Frame w/ Brackets for Huck Bolt-On Hanger Installation	Aluminum Cabinets	48" Curbside Operation Cabinet
Suspension Tandem Axle / Tandem Dolly	HENDRICKSON INTRAXX AAT25K 14" RH, HXL-3 Wheel end system, 25,000 LBS Capacity, Bolt-C	Other Accessories	Aluminum Fenders, Aluminum Ladder (1) Aluminum Hose Tubes & More
Font Dolly & Turntable	Heavy Duty Rectangular HSS tube, 36,000 lbs Turntable, 43" double race ball bearings.	Documents	All Test & Certifications Documents Completed & Provide to the Customer